TBR-12&2455

For 1.2 / 2.4 GHz Selectable

Portable RF Sender/Receiver Kit

Feature

Wired covert cameras double its value when work in conjunction with Portable Wireless A/V Transmitter & Receiver Kit and become wireless cameras.



Brilliant looking & Rugged design made by Mag-Aluminum alloy housing, compact enough to carry & great solution for heat sink

Both Transmitter & Receiver utilizes 2200mAh ultra high capacity removable standard FUJI camcorder lithium battery

Single general stereo jack socket on transmitter for A/V signal output and power supply, hassle free on cable plugging

Friendly operated by power/charge LED & low-batt. vibration alert while along with the easy CH-Dip-Switch via equipped sticker tool

Specification

Tranmitter	
Item Number	TB-1255CK & TB-2455CK
Frequency Band	1.2 & 2.4 GHz
Available Channel	6 CH's @ 1.2 GHz / 8 CH's @ 2.4GHz
Output Power	500 mW
Battery	2200 mA / 3.7 V Lithium
Battery Charge Time	120 Minutes
Battery Life Time	2 Hours
Weight	65 g
Dimension	78x66x15 mm
Receiver	
Receiver Item Number	RX-1280BCK & RX-2480BCK
	RX-1280BCK & RX-2480BCK 1.2 & 2.4 GHz
Item Number	
Item Number Frequency Band	1.2 & 2.4 GHz
Item Number Frequency Band Available Channel	1.2 & 2.4 GHz 8 CH's
Item Number Frequency Band Available Channel Antenna	1.2 & 2.4 GHz 8 CH's 3 dbi SMA Detacheable
Item Number Frequency Band Available Channel Antenna Battery	1.2 & 2.4 GHz 8 CH's 3 dbi SMA Detacheable 2200 mA / 3.7 V
Item Number Frequency Band Available Channel Antenna Battery Battery Charge Time	1.2 & 2.4 GHz 8 CH's 3 dbi SMA Detacheable 2200 mA / 3.7 V 120 Minutes







Standard Accessories









S-1R2R AV Cable

Battery Pack x 2



1.2 or 2.4GHz Ant. x 2