

LOKI NANO



Tactical PTZ Caméra : COMPACT CAMERA



Description :

- Nano camera PTZ Full HD 1080p 2.38MP
- Optical Zoom 10X (5~51mm)
- Minimum illumination 0.001 Lux @ (DSS ON B/W)
- Rotation 360° endless
- Ø 85mm x 120mm
- NDAA Compliant
- Warranty 2 ans

LOKI-NANO IP67 waterproof HD-IP compact camera ONVIF.

This camera is designed for tactical applications and covers a wide range of covert surveillance operations.

It includes an Ethernet interface to transmit surveillance images with a resolution of 1080p@25fps.

This camera has a PTZ functionality with a continuous 360° rotation and a vertical tilt of 30°.

This HD-IP camera can be easily concealed to meet the requirements of tactical surveillance.

Allwan Security also offers tactical solutions for recording and long-distance 4G/5G transmissions.

Specifications

LOKI NANO : Caméra PTZ 10X 2MP ONVIF	
Sensor	1/2.8" SONY Exmor R CMOS
Optical Zoom	10X optical + 12X digital
Focal	5 ~ 51mm
Field of view	57.7°(Wide) à 6.4° (Télé)
Minimum illumination	0.001 Lux @ (DSS ON B/W)
Electronic Shutter	50Hz: 1~1/30,000s; 60Hz: 1~1/30,000s
Day/Night	IR-CUR filter
Video	Compression H.264 H/265 BP/MP/HP, H.265 main profile, MJPEG
Resolution	Full HD/1080P (1920x1080)
Frame rate per second	MAX 30fps
Bandwidth	32Kpbs~8 Mbps on each video channel 3 Video Streams Format H.264/ H.265 VBR/CBR
Supported protocols	IPv4, TCP/IP, UDP, HTTP, DHCP, RTP/RTCP/RTSP, FTP, UPnP, DDNS, NTP, IGMP, ICMP, ONVIF, GB/T 28181
PTZ Preset	Non
Protection	IP67
Working Temperature	-10°C to +55°C
Ethernet Cable	2m cable X-Code M12 to RJ45 IP67
Dimensions	Ø 85 X 120 mm
Alimentation	12V DC ± 10% - (Option PoE 802.3af)
Weight	1 Kg (sans valise)
Consumption	< 6W
Warranty	2 Years return to workshop

