

DVR : 960H Standalone DVR Tactical case


- **H.264 Main Profile** compression
- **WD1(PAL:960×576,NTSC:960×480) resolution real-time recording**
- **Live screen 1920×1080P resolution 4-ch synchronous playback**
- **2.5" internal HDDs (>4TB/HDD) or SSD**
- **Gigabit network interfaces Privacy mask**
- **Up to 4 alarm inputs, car speeding pulse input, car engine revolution signal input**
- **Ethernet and USB 3G dongle support for remote access, with Remote :**
- **Free DDNS server**
- **DVR browser utility**
- **Push alarm notification** for portable device
- **Dynamic electronics maps for CMS**
- **Remote setup, monitoring, backup, alarm notification, & remote software upgrade**
- **iPhone/iPad/Mac/Android/MS-Windows** remote software
- **1 I.E./Firefox/Chrome/App** for multiple DVRs
- **Configurable HTTP/SMTP/FTP/Control/Data** port
- **RTSP support**
- **Transmission 3G / 4G & Wifi**

Specifications

960H Standalone DVR Tactical case	
O.S.	Embedded Linux 3.0
Compression	H.264
Analog Video output:	4 Way
Resolution	PAL: 704×576, NTSC: 704×480
Frame Rate:	25fps (P) / 30fps /N
Playback Resolution:	WD1/ 4CIF / 2CIF / CIF / QCIF
USB Interface:	1 USB 2.0 Interfaces front panel
Router	Industrial router Dual SIM/USIM cards
	4G LTE performance up to: 100 Mbps downlink and 50 Mbps uplink (CAT3)
	LTE FDD, B1/B2/B3/B5/B7/B8/B20
	DC-HSPA+/HSPA+/HSPA/UMTS/GSM/GPRS/EDGE
	Simple web interface for configuration
interface	4 X XLR5 video, alim, telemetry
	1 X XLR3 alimentation
	1 X LAN 10/1000 interface
Weight:	3,6 kg
Serial Interface:	RS485 keyboard & camera interface
Working Temperature:	-10°C ~ +55°C (14°F ~ 131°F)
Case	PELI 1400
Dimensions	35 X30 X15 cm

