



The PXR Tactical is thin and light. It is designed to enable accurate inspections in tight places.

The PXR Tactical is engineered for quick and easy setup. A user-friendly interface allows any user to perform inspections in most urgent situations. The PXR Tactical is designed to meet explicitly the needs of the security operators.

Intended to be used by EOD Teams, Counter Surveillance, Customs and Security Operatives.

Sales Code	PXR8903011
Sensor type	Linear CMOS photodiode array
Resolution	1.25 lp/mm (at Magnification 1), 2.23 lp/mm (at Magnification 1.79)
Pixel size	400 µm
Dynamic range	16 bit (65.536 grey levels)
Active area [W × H]	294 mm × 204 mm
External dimensions [W × H × D]	450 mm × 296 mm × 25 mm
Uncovered active area	5 mm (from bottom) and 12 mm (left side)
Weight	3.4 kg, 3.7 kg including battery
Image scanning time	From 6 sec
Power Supply	Li-ion Battery, rechargeable, exchangeable 2.750 mAh, 60 Wh, Mains Power
Battery life	Approx. 600 images
Communication protocols	Wireless 802.11 b/g/n and Wired TCP/IP Ethernet
Organic scan	Yes
Operation modes	Horizontal, vertical, any angle
Operating temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Storage temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Protection level	IP 55
Certification and Standards	CE, EN 61010-1:2010, EN 61326-1:2013, EMC 2014/30/EU, IEC60068-2-2 (Heat); IEC60068-2-1 (Cold), IEC 60529 (2013-08)