

UW-38AHD Underwater camera SST 316L - 2.1Mp**Specifications :**

UW-38iTVI	
Sensor	1/2.7" 2,1Mp
Resolution	1080p 25fps
Pixels	1920 x 1080
Video output	AHD
Angle of view	90° in air
Minimum illumination	0,2 Lux
BLC	Automatic
WB	3200°K ~ 8000°K auto
Gain Control	4 dB ~ 32 dB Auto
Shutter Speed	PAL 1/25 ~ 1/30.000 sec
Light	Yes, up to 10 meters
Power supply	12V DC +/-10% (not provided)
Power consumption	120mA max
Lens	3,6mm standard (4,3 ; 6 ; 8 mm on request)
Working temperature	-10° ~ + 50 ° C
Humidity	90% RH
Dimensions	Ø40 mm X 145 mm
Cable	By meter
body / window	Stainless steel 316L / Window sapphire crystal

- **Maximum working depth 200m**
- **Full HD 1080p**
- **White leds up to 10 meters illumination**
- **Body 100% Stainless steel 316L machined**
- **Electro-polished finish body**
- **Scratch resistant window in sapphire crystal**
- **U mounting bracket as an option**

Options**UW-38iAHD-JUP** : With Jupiter connector**UW-38iAHD-TRPE** : With SubConn underwater connector