WMOBILE1200RS



Digital wireless video and data transmission set

Suitable for Orlaco cameras AF-Z, cranes



This wireless system is designed for Orlaco analogue systems. Thanks to its full automatic frequency selection this is a plug and play set up to 10 in the same area*.

The IP67 housing is full waterproof against rain and dust.

Max wireless range is 150m.

Description

- Chocs and vibrations resistant
- Digital system
- Up to 10 sets in the same area*
- 150m max wireless range
- Power : 12-32VDC
- Video stream at 4Mbps



- 1 : Video signal
- $2: Video\ ground$
- 3 : Power 12-32V
- 4 : Ground
- 5 : RS232 RX / RS485A
- 6: RS232 TX / RS485B





WMOBILE1200RS: Wireless video and data transmission system	
Power	9-32VDC – 4.5W
Video signal	Analogue PAL/NTSC, AHD
Frequencies	2400-2483,5Mhz (Video) 2412-2484 Wifi (Serial link)
Transmission range	150m
Wireless power	20dBm
Video compression	MPEG4
Bitrate	4/12Mbps
Spectral	FHSS 1200/s
Material	Acetal
Mounting	Brackets provided
Serial	WMOBILE1200RS232: RS232 2 wires WMOBILE1200RS485: RS485 2 wires The baudrate is set at 9600Bps at factory, others on demand
Ingress Protection	IP67
Working temperature	-20 à +70°C - RH90%
Storage temperature	-30 à +80°C - RH90%
Connectors	Transmitter: Binder 7cts 723 female – Binder 8cts male (power) Receiver: Binder 7 cts male

*max sets in the same area depends of wireless interferences. We recommend to not exceed 6 to 8 sets.









