

ZB-1980LED and ZB-1988LED

Mini camera Stainless steel 316L Full HD, IP68
Without or with connector, white Leds, 1080p



ALLWAN SECURITY manufactures industrial and underwater video cameras for more than 20 years, introduces its ZB-1980LED and ZB-1988LED inspection camera for industrial applications.

Ultra compact for hard places, it has white leds and a focus set from 5cm to 1000cm.

Enjoy with the clear video images thanks to the 1080p video resolution.

Fully waterproof IP68, up to 200m underwater.

Extension cables 20m and 50m sold separately.

Technical specifications

ZB-1980LED / ZB-1988LED: IP68 SST 316L underwater mini camera Full-HD		
	ZB-1980LED	ZB-1988LED
Sensor	2Mp SONY	
Lens	140° in air	120° in air
Pixels	1920x1080	
Resolution	Full-HD	
Sensibility	0,0001 Lux Color	
Focus	Default : 5-1000cm Option : 20cm to infinite	
S/N ratio	> 65dB	
Video output	Video AHD on BNC 75 ohm connector	
Cable output	Cable gland	Connector
Power	12VDC +/- 10%	
Consumption	120mA	
Working temperature	-20 à +60°C	
Ingress	IP68 – Max 200m depth	
Dimensions	Diam. 23mm x 53mm	Diam. 34mm x 59mm
Accessories	Default cable lenght : 20m	88RALL20U : Ext cable 20m PU diam. 5mm
	Up to 200m on request	88RALL50U : Ext cable 50m PU diam. 5mm
	LUMISS portable monitors/recorders Exists in Delrin on special order (min 5 units)	LUMISS portable monitors/recorders Exists in Delrin on special order (min 5 units)

Description

- 2Mp SONY sensor
- SST 316L body
- Waterproof IP68 – Up to 200m depth
- Leds Hi power
- Video signal BNC TVI (AHD CVI or CVBS analogue on demand)
- Cable gland on ZB-1980LED / Connector on ZB-1988LED
- Angle of view H 120/140° in air



Optional LUMISS100 monitor with dedicated connector

