UW-POOLHD47



Flush mounting underwater IP camera for swimming pools

Max underwater 50m - hubcap in PVC or Stainless steel



Anti-drowning video camera for swimming pool surveillance, especially designed to be installed like a spotlight in swimming pools.

Permanently underwater up to 50m.

Perfect for swimmers, our camera can also be used to industrial applications.

As option: fill body in SST 316L (1.4404), and/or hubcap in SST 316L.

This camera is delivered with its flush mountting kit suitable for Chlorine.

Cable by meter, delivered pre-installed on each camera.

Chroline stabilized max 4mg/L.

Technical specifications:

UW-POOLHD47 : Underwater pool camera	
Weight	805g without flush mounting kit
IP incide	IP68 – 50m permanently
Material	Camera module : PVC (option SST 316L) Hubcap : PVC (White, black, grey), SST 316L option
Video sensor	CMOS 2,43Mp
Resolution	2,43Mp (matrix 2000x1240) Video output 1920*1080 – 25 fps
DAY/NIGHT	YES
IRIS	Automatic
Sensibility	Color: 0.1Lux / BW: 0.1Lux
Digital enhancement	BLC; AGC
Video output	Ethernet
Window	Polycarbonate or cristal saphire as option
Lens	2.8mm 114° H in air > 81° in water
Flush mounting	Niche in bronze, SST V4A or PVC fourni > For concrete pool or liner (needs accessory sold separately)
Heater	No needed
Working temperature	-10 à +50°C
External diameter	325mm (others dimensions as option)
Camera module dimensions	Diameter 90 x 98 mm
Cable	marine PU, by meter
Power supply	POE 12V, injector provided
Stream	OnVif - RTP and RTSP Compatible Milestone, Hik, Seetec and others

Description

- Especially designed for pool surveillance
- High resolution 2,43Mp
- Hubcap in Stainless steel 316L (option) or PVC
- Cable gland special for underwater applications
- OnVif, RTSP and RTP
















Flush mounting underwater IP camera for swimming pools

Max underwater 50m – hubcap in PVC or Stainless steel











Niche provided for Liner or concrete.

Possibility to use your own niche, depending of compatiility

