

UW-IMSTOR

Underwater PTZ camera, IP HD 2Mp 1920x1080 Ethernet – OnVif



The UW-IMSTOR ALLWAN SECURITY camera offers Full HD resolution at 1920x1080 thanks to its 2MP sensor, suitable for all situations. Its robust casing allows for underwater use up to 90m.

- 2MP resolution
- 12x optical zoom lens
- 90m immersion
- Delrin and brass body (other materials available upon request)
- Subconn DBH13M connector
- OnVif compliant

The RTSP stream allows viewing with any computer under Microsoft Windows, and recording can be done with simple software like VLC available for free online, or using its WEB page. The camera is also compatible with all OnVif-compliant NVRs on the market.



Specifications :

UW-IMSTOR	
Camera	
Max pressure	9bars (90m)
Material	Delrin and brass Polycarbonate dome On demand : SST, aluminum, cupro-aluminum, titanium
Cable output	SubConn DBH13M
Weight	6,5Kg in air – 3Kg in water
Video	
Sensor	2Mp –CMOS 1/2.8"
Resolution	1080p @25/30fps
Coding	H.265/264 : 30/25fps (60/50Hz) OnVif, RTP, RTSP, UDP
Minimum illumination	0.005Lux
Lens	Optical zoom 12x Angle of view : 58~4.8° Minimum working distance depending of zoom 100-1000mm
NETWORK	
Protocols	IPv4, IPv6, TCP/IP, RTP (UDP), RTP (TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL, DHCP, FTP, SMTP, ICMP, IGMP, SNMP, DNS, DDNS, QoS, UPnP, Bonjour
Interface	100Base-T Ethernet
Video Compression	H.265/H.264/MJPEG
Video standard	ONVIF
GENERAL	
Dimensions	192 x 200
Power Supply	POE 802.3at
Max cable length	85m
Working temperature	0 à +50°C

