

Vision is
our mission®

Camera AMOS CPH 51°PAL
Article no. 0199700
Camera AMOS CPH 51°PAL 0.2B
Article no. 0199710
2016 • DS0199700 EN R1-1


Product Data



Dimensions

units in mm

Length 200/600mm



TECHNICAL DATA

Camera AMOS CPH 51° PAL

Camera AMOS CPH 51° PAL 0.2B

Article number	0199700	0199710
Cable length	600mm	200mm
Weight	0,300kg	0,250kg
Lens specified	51° horizontal, and 38° vertical.	

Description

Video signal	PAL Standard, 1,0Vpp. composite video at 75Ω.
Sensor element	1/4" CMOS digital image sensor. 640(H) x 480(V).
Light sensitivity	<0,05 Lux.
Dynamic range	80dB.

Sensor

Power input	Stabilised 12V/DC.
Power consumption	<+15°C: 3W and >+15°C: 1,2W (heating off).
Cable	Multicable with 4 pins molded male connector (camera power-input and video-output).
Min. cable bend radius	50mm.

Electrical


Housing	Stainless steel 316.
Lens glass	2 mm chemically hardened, toughened, tempered float glass 7 x stronger than ordinary glass with anti reflective coating.
Protection	IP68 according to IEC 60529 (up to 10m under water). IP69K according to DIN 40050-9, camera housing can withstand high pressure cleaning with water; 14-16L/min. 80°C and 100 bars flow.
Shock constancy	Shock and vibration resistant for usage on forks of forklift trucks, 50G shock test and 15G random vibration test.
Mounting hardware	Standard stainless steel.
Operating temperature	-40°C to +85°C.
Storage temperature	-40°C to +125°C.

Mechanical

Certification

Approvals Product is in compliance with the EMC directive.

Electrical connections



Front side 4p molded male connector

- | | |
|--------------------|-------------|
| 1 = Coax core | = video |
| 2 = Coax shielding | = Video GND |
| 3 = Red | = 12V/DC |
| 4 = Black | = 0V |
| Shield | = GND |

All data subject to change without notice. All dimensions are for commercial purpose only.
The camera/display systems from Orlaco comply with the latest CE, ADR, EMC and mirror-directive regulations, where applicable.
All products are manufactured in accordance with the ISO 9001 quality management system, ISO/TS 16949 quality automotive, ISO 14001 environmental management systems and all Ex products with the IECEx scheme and ATEX directives, where applicable.

