

MO-1006AL

6,5" Panel mount monitor

Industrial and High Brightness



ALLWAN

VIDEO & SECURITY SOLUTIONS



DESCRIPTION

- Active area 6.5" (132.5 x 99.4 mm)
- Front side Ip65
- Reinforced steel frame
- Standard VGA/ HDMI input – DVI option
- Resolution 640 x 480
- Brightness 700 nits
- Optional resistive touch panel



The compact 6.5" high brightness monitor is perfectly suited to industrial conditions, it seduces with its robustness, image quality and long lifespan.

The optional anti-shock glass promises extreme resistance to shocks.

Technical Characteristics

MO-1006AL

DISPLAY	
Resolution	640 x 480
Size	6,5"
Colors	16.2 Million colors
Active Area	132,48 x 99,36 mm
Brightness	700 nits
Contrast	600 :1
Viewing angles	80, 80, 70, 70°
Options: Touch/ Protection	Optional touch: Resistive touch panel Optional Protection: Glass pane (no touch possible)
PORTS	
Video Inputs	VGA/ HDMI – Optional DVI
Option: Audio	Option line input 3.5mm jack with 2 built-in HP
ELECTRICAL/ MECHANICAL	
Dimensions	218 x 164 x 50mm
Ingress Protection	IP65 Front side
Materials	Steel frame – Aluminum bezel
Panel cutting	191 x 143
Mounting	Panel or rear VESA 75
Power	12VDC 2A
Weight	1.2Kg
Certifications	CE, FCC
ENVIRONMENT	
Working Temperature	0 to +50°C
Storage Temperature	-10 at +60°C
Humidity	10% to 90% moisture – Not condensed

MO-1006AL

6,5" Panel mount monitor

Industrial and High Brightness



ALLWAN

VIDEO & SECURITY SOLUTIONS



DIMENSIONS

