

MO-1010AL

10,4" Panel mount monitor

Industrial & High Brightness



ALLWAN

VIDEO & SECURITY SOLUTIONS



DESCRIPTION

- Active area 10.4" (210.4 x 157.8 mm)
- Front side IP65
- Reinforced steel frame
- Standard VGA/ HDMI input – DVI option
- 1024 x 768 Resolution
- Brightness 1000 nits
- Optional resistive touch panel

The compact 10.4" monitor is reinforced and perfectly adapted to industrial conditions, it seduces with its robustness, image quality and long life.
The optional anti-shock glass promises extreme resistance to shocks.



Technical Characteristics

MO-1010AL

DISPLAY	
Resolution	1024 x 768
Size	10,4"
Colors	16.2 Million colors
Active area	210,4 x 157,8 mm
Brightness	1000 nits
Contrast	1000 :1
Viewing angles	88, 88, 88, 88°
Options: Touch/ Protection	Optional touch: Resistive touch screen Optional Protection: Glass panel (no touch possible)
PORTS	
Video Inputs	VGA/ HDMI – Optional DVI
Option: Audio	Option line input 3.5mm jack with 2 built-in HP
ELECTRICAL/ MECHANICAL	
Dimensions	284 x 234 x 43 mm
Ingress Protection	IP65 Front side
Materials	Steel frame – Aluminum bezel
Panel cutting	264 x 216 mm
Mounting	Panel or rear VESA 75
Power	12VDC 2A – 24VDC OPTION
Weight	1.5Kg
Certifications	CE, FCC
ENVIRONMENT	
Working Temperature	0 to +50°C – Exists in wide temperature range -20 to +60°C (MO-1010AL-WT)
Storage Temperature	-10 at +60°C
Humidity	10% to 90% moisture – Not condensed

MO-1010AL

10,4" Panel mount monitor

Industrial & High Brightness



ALLWAN

VIDEO & SECURITY SOLUTIONS



DIMENSIONS

