

MO-1015AL

15" Panel mount monitor

Industrial & High Brightness



ALLWAN

VIDEO & SECURITY SOLUTIONS



DESCRIPTION

- Active area 15" (304.1 x 228.1 mm)
- Front side IP65
- Reinforced steel frame
- Standard VGA/ HDMI input – DVI option
- 1024 x 768 Resolution
- Brightness 1000 nits
- Optional resistive touch panel

The 15" reinforced compact monitor is perfectly suited to industrial conditions, it seduces with its robustness, image quality and long lifespan. The optional anti-shock glass promises extreme resistance to shocks.



Technical Characteristics

MO-1015AL

DISPLAY	
Resolution	1024 x 768
Size	15"
Colors	16.2 Million colors
Active area	304,1 x 228,1 mm
Brightness	1000 nits
Contrast	2000 :1
Viewing angles	88, 88, 88, 88°
Options: Touch/ Protection	Optional touch: Resistive touch screen Optional Protection: Glass panel (no touch possible)
PORTS	
Video Inputs	VGA/ HDMI – Optional DVI
Option: Audio	Option line input 3.5mm jack with 2 built-in HP
ELECTRICAL/ MECHANICAL	
Dimensions	400 x 320 x 49,8 mm
Ingress Protection	IP65 Front side
Materials	Steel frame – Aluminum bezel
Panel cutting	360 x 280 mm
Mounting	Panel or rear VESA 75
Power	12VDC 2A – 24VDC OPTION
Weight	4Kg
Certifications	CE, FCC
ENVIRONMENT	
Working Temperature	0 to +50°C – Exists in wide temperature range -20 to +60°C (MO-1015AL-WT)
Storage Temperature	-10 at +60°C
Humidity	10% to 90% moisture – Not condensed

MO-1015AL

15" Panel mount monitor

Industrial & High Brightness



ALLWAN

VIDEO & SECURITY SOLUTIONS



DIMENSIONS

