

MO-1019AL

19" Panel mount monitor

Industrial & High Brightness



ALLWAN

VIDEO & SECURITY SOLUTIONS



DESCRIPTION

- Active surface area 19" (376.3 x 301 mm)
- Front side IP65
- Reinforced steel frame
- Standard VGA/ HDMI input – DVI option
- Resolution 1280 x 1024
- Brightness 1000 nits

The reinforced 19" monitor is perfectly suited to industrial conditions, it seduces with its robustness, image quality and long life.

The optional anti-shock glass promises extreme resistance to shocks.



Technical Characteristics

MO-1019AL

DISPLAY	
Resolution	1280 x 1024
Size	19"
Colors	16.7 Million colors
Active area	376,3 x 301 mm
Brightness	1000 nits
Contrast	1000 :1
Viewing angles	85, 85, 80, 80°
Options: Touch/ Protection	Optional touch: Resistive touch screen Optional Protection: Glass panel (no touch possible)
PORTS	
Video Inputs	VGA/ HDMI – Optional DVI
Option: Audio	Option line input 3.5mm jack with 2 built-in HP
ELECTRICAL/ MECHANICAL	
Dimensions	474 x 384 x 59 mm
Ingress Protection	IP65 Front Side
Materials	Steel frame – Aluminum bezel
Panel cutting	446 x 356 mm
Mounting	Panel or rear VESA 75
Power	12VDC 2A – 24VDC OPTION
Weight	6.5Kg
Certifications	CE, FCC
ENVIRONMENT	
Working Temperature	0 to +50°C – Exists in wide temperature range -20 to +60°C (MO-1019AL-WT)
Storage Temperature	-10 at +60°C
Humidity	10% to 90% moisture – Not condensed

MO-1019AL

19" Panel mount monitor

Industrial & High Brightness



ALLWAN

VIDEO & SECURITY SOLUTIONS



DIMENSIONS

