

MO-1022AL

22" Panel mount monitor

Industrial & High Brightness



ALLWAN

VIDEO & SECURITY SOLUTIONS



DESCRIPTION

- Active area 21.5" (476.6 x 268.1 mm)
- Front side IP65
- Reinforced steel frame
- Standard VGA/ HDMI input – DVI option
- 1920 x 1080 Resolution
- Brightness 1000 nits
- Optional resistive touch panel

The reinforced 22" monitor is perfectly suited to industrial conditions, it seduces with its robustness, image quality and long life.

The optional anti-shock glass promises extreme resistance to shocks.



Technical Characteristics

MO-1022AL

DISPLAY	
Resolution	1980 x 1080
Size	21,5"
Colors	16.7 Million colors
Active area	476,6 x 268,1 mm
Brightness	1000 nits
Contrast	5000 :1
Viewing angles	89, 89, 89, 89°
Options: Touch/ Protection	Optional touch: Resistive touch screen Optional Protection: Glass panel (no touch possible)
PORTS	
Video Inputs	VGA/ HDMI – Optional DVI
Option: Audio	Option line input 3.5mm jack with 2 built-in HP
ELECTRICAL/ MECHANICAL	
Dimensions	534 x 349 x 66 mm
Ingress Protection	IP65 Front side
Materials	Steel frame – Aluminum bezel
Panel cutting	510 x 325 mm
Mounting	Panel or rear VESA 75
Power	12VDC 2A – 24VDC OPTION
Weight	6.3Kg
Certifications	CE, FCC
ENVIRONMENT	
Working Temperature	0 to +50°C
Storage Temperature	-10 at +60°C
Humidity	10% to 90% moisture – Not condensed

Industrial & High Brightness

