



TI-GEAR-S



Meet the legendary GSCI quality in the new line of thermal imagers. TI-GEAR-S is the high-performance thermal weapon sights. Suitable for any mission in any environment, this easy to use, plug-and-play system is a cost-effective tool for observation, aiming and engagement in both broad daylight and extreme darkness on almost any firearm.

ADVANTAGES OF TI-GEAR-S

High-Performance, Auto-NUC, Shutterless, Silent FPA

Smooth and Precise Focus Adjustment

Fast Germanium
Objective Lenses

Ergonomic and User-Friendly Keypad

Canadian-Made, ITAR-Free System, Available for Export

Comfortable Eyepiece with Long Eyerelief

Full-Size Colour AMOLED Display

Multi-Use MIL-STD-1913 Side Mounting Bracket

Multiple Weapon Mounts Available



All-Aluminum Rugged Housing







Designed, Developed, Manufactured by GENERAL STARLIGHT COMPANY INC.

120 WHITMORE ROAD, UNIT 20, WOODBRIDGE, ONTARIO, L4L6A5, CANADA

WWW.GSCI1.COM | GSCI@GSCI1.COM | +1.905.850.0990





TI-GEAR-S

TECHNICAL DATA				
	TI-GEAR-S335	TI-GEAR-S635		
Optical Magnification	2.1X	1.4X		
Objective Lens	35mm, f/1.0			
Field of View	10.6°x8°	17.7°x13.3°		
Focusing Range	0.5m Infinity			
Diopter Adjustment Range	-6 +4			
FPA Resolution	384x288	640x480		
FPA Type, Pitch	Uncooled, a-Si, Shutterless, Silent, Auto-NUC (Uninterrupted Operation), 17µm			
FPA Sensitivity	<60mK			
FPA Refresh Rate	50Hz			
Digital Zoom	1X, 2X, 4X	1X, 2X, 4X, 8X		
Internal Display	AMOLED, Colour, 800x600, 0.6" Diagonal			
Imaging Modes	1 Monochrome + 8 Colour			
Electronic Reticles	Yes: 7 patterns			
Video Recorder	Optional: External with SD Card			
Detection Man (1.7x0.5m) / Vehicle (2.3x2.3m)	1000m / 1350m			
Accepted Batteries	2 (two) CR123 of Any Type: Lithium, Ni-MH, Alkaline, etc.			
Universal Port	Yes: Video-Out and External Power (4VDC 15VDC)			
Battery Life	Up to 7 Hours			
Environmental Protection	IP66 or Better (Optional)			
Dimensions	158 x 60 x 59 mm (6.22 x 2.36 x 2.32 in)			
Weight	433 grams (15.27 oz)			
Operating Temperature	-40°C +50°C			
Warranty	7 Years, Limited			
Export	Available Worldwide (Canadian Export Permit Required. GSCI provides assistance in obtaining the Permit)			





TI-GEAR-S

TECHNICAL DATA				
	TI-GEAR-S350	TI-GEAR-S650		
Optical Magnification	3X	2X		
Objective Lens	50mm, f/1.3			
Field of View	7.5°x5.6°	12.4°x9.3°		
Focusing Range	1m Infinity			
Diopter Adjustment Range	-6 +4			
FPA Resolution	384x288	640x480		
FPA Type, Pitch	Uncooled, a-Si, Shutterless, Silent, Auto-NUC (Uninterrupted Operation), 17µm			
FPA Sensitivity	<60mK			
FPA Refresh Rate	50Hz			
Digital Zoom	1X, 2X, 4X	1X, 2X, 4X, 8X		
Internal Display	AMOLED, Colour, 800x600, 0.6'' Diagonal			
Imaging Modes	1 Monochrome + 8 Colour			
Electronic Reticles	Yes: 7 patterns			
Video Recorder	Optional: External with SD Card			
Detection Man (1.7x0.5m) / Vehicle (2.3x2.3m)	1660m / 2250m			
Accepted Batteries	2 (two) CR123 of Any Type: Lithium, Ni-MH, Alkaline, etc.			
Universal Port	Yes: Video-Out and External Power (4VDC 15VDC)			
Battery Life	Up to 7 Hours			
Environmental Protection	IP66 or Better (Optional)			
Dimensions	172 x 60 x 59 mm (6.77 x 2.36 x 2.32 in)			
Operating Temperature	-40°C +50°C			
Warranty	7 Years, Limited			
Export	Available Worldwide (Canadian Export Permit Required. GSCI provides assistance in obtaining the Permit)			





TI-GEAR-S

TECHNICAL DATA				
	TI-GEAR-S350F	TI-GEAR-S650F		
Optical Magnification	3X	2X		
Objective Lens	50mm, f/1.0			
Field of View	7.5°x5.6°	12.4°x9.3°		
Focusing Range	1m Infinity			
Diopter Adjustment Range	-6 +4			
FPA Resolution	384x288	640x480		
FPA Type, Pitch	Uncooled, a-Si, Shutterless, Silent, Auto-NUC (Uninterrupted Operation), 17µm			
FPA Sensitivity	<60mK			
FPA Refresh Rate	50Hz			
Digital Zoom	1X, 2X, 4X	1X, 2X, 4X, 8X		
Internal Display	AMOLED, Colour, 800x600, 0.6'' Diagonal			
Imaging Modes	1 Monochrome + 8 Colour			
Electronic Reticles	Yes: 7 patterns			
Video Recorder	Optional: External with SD Card			
Detection Man (1.7x0.5m) / Vehicle (2.3x2.3m)	1660m / 2250m			
Accepted Batteries	2 (two) CR123 of Any Type: Lithium, Ni-MH, Alkaline, etc.			
Universal Port	Yes: Video-Out and External Power (4VDC 15VDC)			
Battery Life	Up to 7 Hours			
Environmental Protection	IP66 or Better (Optional)			
Dimensions	172 x 60 x 60 mm (67.7 x 23.6 x 23.6 in)			
Operating Temperature	-40°C +50°C			
Warranty	7 Years, Limited			
Export	Available Worldwide (Canadian Export Permit Required. GSCI provides assistance in obtaining the Permit)			



TECHNICAL DATA				
	TI-GEAR-S375	TI-GEAR-S675		
Optical Magnification	4.5X	3X		
Objective Lens	75mm, f/1.3			
Field of View	5.0°x3.7°	8.3°x6.2°		
Focusing Range	2m Infinity			
Diopter Adjustment Range	-6 +4			
FPA Resolution	384x288	640x480		
FPA Type, Pitch	Uncooled, a-Si, Shutterless, Silent, Auto-NUC (Uninterrupted Operation), 17µm			
FPA Sensitivity	<60mK			
FPA Refresh Rate	50Hz			
Digital Zoom	1X, 2X, 4X	1X, 2X, 4X, 8X		
Internal Display	AMOLED, Colour, 800x600, 0.6" Diagonal			
Imaging Modes	1 Monochrome + 8 Colour			
Electronic Reticles	Yes: 7 patterns			
Video Recorder	Optional: External with SD Card			
Detection Man (1.7x0.5m) / Vehicle (2.3x2.3m)	2500m / 3380m			
Accepted Batteries	2 (two) CR123 of Any Type: Lithium, Ni-MH, Alkaline, etc.			
Universal Port	Yes: Video-Out and External Power (4VDC 15VDC)			
Battery Life	Up to 7 Hours			
Environmental Protection	IP66 or Better (Optional)			
Dimensions	193 x 66 x 66 mm (7.6 x 2.6 x 2.6 in)			
Weight	498 grams (17.56 oz)			
Operating Temperature	-40°C +50°C			
Warranty	7 Years, Limited			
Export	Available Worldwide (Canadian Export Permit Required. GSCI provides assistance in obtaining the Permit)			





TI-GEAR-S

STANDARD EQUIPMENT: WHAT'S IN THE BOX



TI-GEAR-S Unit Quick Release Weapon Mount Included *



Video-Out Cable



USB Power Cable



Soft Pouch



Hard Case



User Manual



Quick Reference Card



Warranty Form

OPTIONAL EQUIPMENT





MAK Weapon Mount: Available in Picatinny and BLASER versions (comes with regular- or extended length adapter)



Video Recorder with SD Card





Portable Head-Mounted Display HMD-800 (streams thermal video directly from the device)

DISCLAIMER. Technical description, view, weight, dimensions, some optical-electronic-mechanical features of the product shown herein and/or some of its parts/components may not precisely represent the actual device and are subject to change without prior notice by the sole discretion of General Starlight Company, Inc.

^{*} MAK Picatinny or BLASER mount is included with 75mm models