

Tactical PTZ camera: SATIS



Description

- * Mini PTZ Camera – Rugged & Sealed IP66
- * Optical Zoom 30 X + Digital Zoom 12X
- * 1/2.8" Progressive Scan CMOS
- * High resolution 1080p@25 fps - 2 Megapixels
- * 360° Continuous Rotation
- * Flip + Mirror Functions
- * Pre-sets are saved in case of power loss.
- * No initialisation of the pan / tilt cycle at start-up.
- * Passive PoE 12VDC
- * 2-year warranty

Allwan Security, has launched a new high-performance HD-IP Periscope camera. Designed for law enforcement applications covering a wide range of mobile or fixed covert surveillance operations, the camera will deliver a reliable and flexible performance in all weather conditions.

This new camera includes an Ethernet interface for transmitting surveillance images with a resolution of 1080p at 25 fps.

With Pelco-D telemetry RS485 compatibility, the camera has full PTZ functionality with 360° pan and 60° tilt with continuous rotation. An innovative motor drive system allows precise positioning control even when panning at high speed (low latency).

This new HD-IP camera can be easily hidden, providing high quality images and meeting the requirements of tactical surveillance.

Allwan Security also offers a 4G tactical case for recording and transmission.

Specifications:

SATIS	
Zoom Module	30X = 4.5-135 mm
Aperture Range	F1.6 to F4.4
Angle of View	65.1° to 2.34°
Image Sensor	1/2.8" 2MP Progressive scan CMOS
Minimum Illumination	Colour: 0.05Lux @ (F1.6, AGC ON), ICR ON B/W: 0.01Lux @ (F1.6, AGC ON), ICR OFF
Shutter	1/1 s to 1/30,000
WDR	120dB
Day / Night	Auto/Colour/NB
Video Compression	H.264/H.265
Max. Image Resolution	1080p25fps
Network Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, FTP, 802.1x, QoS, HTTPS, IPv6 (SIP, SRTP optional)
Storage Capability	128GB
Protection	IP66
Housing	Acetal Homopolymer, black anodized aluminium, polycarbonate glass
Working Temperature	-10°C to +55°C
Connectivity	2.5m cable (RJ45/BNC/XLR5/Jack 2.1)
Dimensions	Ø 89 mm X 270 mm
Power Requirements	12V DC POE - (Option PoE 803.11AF 48V DC)
Weight	1.9 Kg (without the tactical case)
Power Consumption	< 6W
Transport	Tactical Case



Ultra Low-light