

ZB1902

4 in 1 bullet IP67 camera with OSD

AHD, CVI, TVI and CVBS



The new ZB1902 mini bullet camera is IP67 waterproof, has an OSD menu to choose the video signal output (TVI as default), and offers a lot of digital settings as WDR, Defog, 3D DNR.

Description

- Sony 1/2.8" 2.13MP Progressive Scan STARVIS CMOS
- 1080p(1920x1080)@30(25)fps
- 4in1 Output(AHD, TVI, CVI, CVBS)
- Fixed lens 3.6mm
- Electronic Day&Night
- WDR, 3D DNR, Defog
- OSD control
- Only 19mm diameter

Technical specifications :

ZB1902 : mini bullet 1080p camera	
Image sensor	1/2.8" Progressive Scan SONY STARVIS CMOS
Effective pixels	1945(H) x 1097(V)
Max video resolution	TVI, AHD, CVI : 1080p@30(25)fps/720p@60fps(50fps)/720p@30fps(25fps) TV out: CVBS(720H) NTSC/PAL
Lens	Fixed lens 3.6mm F2.0 M12x0.5mm
Minimum illumination	0.2Lux (F2.0,AGC33dB, DSS :x2)
White balance	AUTO/AUTO EXT/PUSH LOCK/MANUAL
Dynamic Range	WDR/BLC : OFF/BLC/HLC/WDR15P/WDR30P D-WDR : OFF/LOW/MIDDLE/HIGH Level : 135.6dB
Electronic Shutter speed	AUTO/FLICKER/MANUAL/(1/30(25)~1/30,000)
DSS	OFF~ x32
AGC	OFF~45dB
Day/Night	AUTO/COLOR/B&W (Electronic D&N)
Noise Reduction	3D-DNR(OFF/LOW/MIDDLE/HIGH)
Motion Detection	OFF/ON(4 Zones)
Privacy Mask	16 Zones
Image rotation	OFF/H-FLIP/V-FLIP/HV-FLIP
Defog	OFF/ON(AUTO/MANUAL)
Sharpness	0~10
OSD Control	Yes, remote joystick provided
Language	ENGLISH,Русский, ESPAÑOL, DEUTSCH, FRANCAISE, PORTUGUÊS, 日本語, 한국어
Video Output	AHD, TVI, CVI, CVBS
IP Rating	IP67
Operating Temperature	-10°C~+50°C
Storage Temperature	-20°C~+60°C
Dimensions	Φ19x54.8mm
Power	12VDC +/-10%

