
AT-HDPTZ





Headrest Set PTZ Camera for surveillance vehicles









Tubes Ø 10/12/14

Specifications:

Sensor2MP 1/2.8" progressive scan CMOSPicture QualityFull 1920 x 1080Zoom25x optical zoom + 12 digitalLensf = 4.8 mm (wide) to 120 mm (tele) F1.6 à F4.4Angle of View1080p 57.6° (wide end) to 2.5° (tele end)Min. Working Distance10 mm (wide end) to 1500 mm (tele end)Min. IlluminationColour: 0.05Lux @ (F1.6, AGC ON) B/W: 0.0 1 Lux @ (F1.6, AGC ON) (Attenuated by the fabric)S/N ratioOver 50 dBShutter1/1 to 1/30,000sWhite BalanceAuto 1/Auto 2/Indoor/Outdoor/Manual/Sodium Lamp/Fluorescent LampGain16 levelsWDROn / OffStorageMicro-SD 128GBIntrusion, line crossing detection, region entrance detection, region exiting detection, unattended baggage detection, object removalFace captureYesFocus systemAuto/Manual/One TouchWorking Temperature-5° C to 60 °CAudioMicrophone (optional)MirrorOn/OffVisions360° endless	AT-HD	
Zoom 25x optical zoom + 12 digital f = 4.8 mm (wide) to 120 mm (tele) F1.6 à F4.4 Angle of View 1080p 57.6° (wide end) to 2.5° (tele end) Min. Working Distance 10 mm (wide end) to 1500 mm (tele end) Colour: 0.05Lux @ (F1.6, AGC ON) B/W: 0.0 1 Lux @ (F1.6, AGC ON) (Attenuated by the fabric) S/N ratio Over 50 dB Shutter 1/1 to 1/30,000s Auto 1/Auto 2/Indoor/Outdoor/Manual/Sodium Lamp/Fluorescent Lamp Gain 16 levels WDR On / Off Storage Micro-SD 128GB Intrusion, line crossing detection, region entrance detection, region exiting detection, unattended baggage detection, object removal Face capture Yes Focus system Auto/Manual/One Touch Working Temperature -5° C to 60 °C Audio Microphone (optional) Mirror On/Off	Sensor	2MP 1/2.8" progressive scan CMOS
F = 4.8 mm (wide) to 120 mm (tele)	Picture Quality	Full 1920 x 1080
F1.6 à F4.4 Angle of View 1080p 57.6° (wide end) to 2.5° (tele end) Min. Working Distance 10 mm (wide end) to 1500 mm (tele end) Colour: 0.05Lux @ (F1.6, AGC ON) B/W: 0.0 1 Lux @ (F1.6, AGC ON) (Attenuated by the fabric) S/N ratio Over 50 dB Shutter 1/1 to 1/30,000s Auto 1/Auto 2/Indoor/Outdoor/Manual/Sodium Lamp/Fluorescent Lamp Gain 16 levels WDR On / Off Storage Micro-SD 128GB Intrusion, line crossing detection, region entrance detection, region exiting detection, unattended baggage detection, object removal Face capture Yes Focus system Auto/Manual/One Touch Working Temperature -5° C to 60 °C Audio Microphone (optional) Mirror On/Off	Zoom	25x optical zoom + 12 digital
Min. Working Distance 10 mm (wide end) to 1500 mm (tele end) Colour: 0.05Lux @ (F1.6, AGC ON) B/W: 0.0 1 Lux @ (F1.6, AGC ON) (Attenuated by the fabric) S/N ratio Over 50 dB Shutter 1/1 to 1/30,000s Auto 1/Auto 2/Indoor/Outdoor/Manual/Sodium Lamp/Fluorescent Lamp Gain 16 levels WDR On / Off Storage Micro-SD 128GB Intrusion, line crossing detection, region entrance detection, region exiting detection, unattended baggage detection, object removal Face capture Yes Focus system Auto/Manual/One Touch Working Temperature -5° C to 60° C Audio Microphone (optional) Mirror On/Off	Lens	` ,
Colour: 0.05Lux @ (F1.6, AGC ON) B/W: 0.0 1 Lux @ (F1.6, AGC ON) (Attenuated by the fabric) S/N ratio Over 50 dB Shutter 1/1 to 1/30,000s Auto 1/Auto 2/Indoor/Outdoor/Manual/Sodium Lamp/Fluorescent Lamp Gain 16 levels WDR On / Off Storage Micro-SD 128GB Intrusion, line crossing detection, region entrance detection, region exiting detection, unattended baggage detection, object removal Face capture Yes Focus system Auto/Manual/One Touch Working Temperature -5° C to 60 °C Audio Microphone (optional) Mirror On/Off	Angle of View	1080p 57.6° (wide end) to 2.5° (tele end)
Min. Illumination B/W: 0.0 1 Lux @ (F1.6, AGC ON) (Attenuated by the fabric) S/N ratio Over 50 dB Shutter 1/1 to 1/30,000s Auto 1/Auto 2/Indoor/Outdoor/Manual/Sodium Lamp/Fluorescent Lamp Gain 16 levels WDR On / Off Storage Micro-SD 128GB Intrusion, line crossing detection, region entrance detection, region exiting detection, unattended baggage detection, object removal Face capture Yes Focus system Auto/Manual/One Touch Working Temperature -5° C to 60 °C Audio Microphone (optional) Mirror On/Off	Min. Working Distance	10 mm (wide end) to 1500 mm (tele end)
Shutter 1/1 to 1/30,000s Auto 1/Auto 2/Indoor/Outdoor/Manual/Sodium Lamp/Fluorescent Lamp Gain 16 levels WDR On / Off Storage Micro-SD 128GB Intrusion, line crossing detection, region entrance detection, region exiting detection, unattended baggage detection, object removal Face capture Yes Focus system Auto/Manual/One Touch Working Temperature -5° C to 60 °C Audio Microphone (optional) Mirror On/Off	Min. Illumination	B/W: 0.0 1 Lux @ (F1.6, AGC ON)
Auto 1/Auto 2/Indoor/Outdoor/Manual/Sodium Lamp/Fluorescent Lamp Gain 16 levels WDR On / Off Storage Micro-SD 128GB Intrusion, line crossing detection, region entrance detection, region exiting detection, unattended baggage detection, object removal Face capture Yes Focus system Auto/Manual/One Touch Working Temperature -5° C to 60 °C Audio Microphone (optional) Mirror On/Off	S/N ratio	Over 50 dB
White Balance 2/Indoor/Outdoor/Manual/Sodium Lamp/Fluorescent Lamp Gain 16 levels WDR On / Off Storage Micro-SD 128GB Intrusion, line crossing detection, region entrance detection, region exiting detection, unattended baggage detection, object removal Face capture Yes Focus system Auto/Manual/One Touch Working Temperature -5° C to 60 °C Audio Microphone (optional) Mirror On/Off	Shutter	1/1 to 1/30,000s
WDR On / Off Storage Micro-SD 128GB Intrusion, line crossing detection, region entrance detection, region exiting detection, unattended baggage detection, object removal Face capture Yes Focus system Auto/Manual/One Touch Working Temperature -5° C to 60 °C Audio Microphone (optional) Mirror On/Off	White Balance	2/Indoor/Outdoor/Manual/Sodium
Storage Micro-SD 128GB Intrusion, line crossing detection, region entrance detection, region exiting detection, unattended baggage detection, object removal Face capture Yes Focus system Auto/Manual/One Touch Working Temperature -5° C to 60 °C Audio Microphone (optional) Mirror On/Off	Gain	16 levels
Intrusion, line crossing detection, region entrance detection, region exiting detection, unattended baggage detection, object removal Face capture Yes Focus system Auto/Manual/One Touch Working Temperature -5° C to 60 °C Audio Microphone (optional) Mirror On/Off	WDR	On / Off
Smart detection detection, region exiting detection, unattended baggage detection, object removal Face capture Yes Focus system Auto/Manual/One Touch Working Temperature -5° C to 60 °C Audio Microphone (optional) Mirror On/Off	Storage	Micro-SD 128GB
Focus system Auto/Manual/One Touch Working Temperature -5° C to 60 °C Audio Microphone (optional) Mirror On/Off	Smart detection	detection, region exiting detection, unattended
Working Temperature -5° C to 60 °C Audio Microphone (optional) Mirror On/Off	Face capture	Yes
Audio Microphone (optional) Mirror On/Off	Focus system	Auto/Manual/One Touch
Mirror On/Off	Working Temperature	-5° C to 60 °C
·	Audio	Microphone (optional)
Visions 360° endless	Mirror	On/Off
	Visions	360° endless
Connectivity RJ45 (PoE 12V passive) Hybrid (optional CBVS)	Connectivity	RJ45 (PoE 12V passive) Hybrid (optional CBVS)
Metal rods Interchangeable depending on the vehicle, the spacing is adjustable	Metal rods	
Power Requirements 12 V DC @ 4,5W	Power Requirements	12 V DC @ 4,5W
Protocol Optional: Pelco-D, Bauds: 2400,4800,9400 Addresses: 1 (default) to 20	Protocol	
Compliant ONVIF	Compliant	ONVIF
Dimensions 27 X 20 X 15.5 cm	Dimensions	27 X 20 X 15.5 cm
Weight 3 kg (headrest with camera)	Weight	3 kg (headrest with camera)

Not homologated for road use

Description:

- Day/Night Camera
- PTZ 360° (H) 60° (V)
- 25x optical motorised zoom
- RJ45, XLR5 (optional)
- Pelco-D
- Sold with an identical empty headrest
- 2-year warranty













- Set of 2 adjustable headrests.
- Only one headrest is equipped with a high-resolution night-vision video camera.
- This head fits most vehicles as the metal rods are adjustable.
- It has been designed in addition to a tactical monitor case or analogue composite recorders.
- 12GB internal memory expandable to 256GB is built-in and allows internal storage.
- Due to its adjustable tilt, the front, rear and side of the vehicle can be monitored. The cables can be directly camouflaged inside the metal rods and into the car seat.
- A 3-metre cable combining video, telemetry and power supply is delivered with a RJ45 and XLR5 connection with the standard Police wiring (1: video, 2: +12V, 3: Mass, 4 & 5: RS485).
- Installation can be done in a few minutes. A control panel with a display screen allows a very quick adjustment from the boot of the vehicle.
- This set can be controlled remotely via Wi-Fi or 3G/4G transmission. The cover is interchangeable with the colour and transparency of your choice (sold separately).
- Our priority is discretion, a black cover for total discretion.
- Turret and electronics 100% French









