## **PXR** Range Extender



The PXR Range Extender allows the PXR Scanning and Flat Panels to connect to a Tablet or Laptop up to 500 m either wired or wireless.

It is a user-friendly plug-and-play solution to increase the safety during operations with dangerous objects and under stressful conditions.

Intended to be used by EOD Teams, Counter Surveillance, Customs and Security Operatives.

Sales code:	PXR8905533
Wired Interface	1 x Proprietary Interface for PXR HUB
	1 x USB2
	1 x Wi-Fi antenna, female N -connector
Wired performance	200 m with supplied cable
	400 m with custom cable
Wireless Interface	802.11 b/g/n 2.4 GHz, Max 19 dBi on antenna port
Wireless performance	Over 100 m line of sight with standard antennas.
	Possibility to extend the reach via high gain antennas.
Data transfer rate	4 Mbit/s, wired connection, up to 433Mbit/s, wireless connection
External dimensions [W × H × D]	115 x90 x 31 mm (not including connectors and antenna)
Weight	600 g (1.3 lb)
Power input	5 V DC, 500mA. Powered from USB.
Operating temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Storage temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Protection level	IP 55
Certification and Standards	CE, 2014/53/EU RED, EU RoHS2
Included in shipment	USB cable

