

Tactical PTZ camera: HERMES



Description

- * PTZ Camera – Rugged & Sealed IP67
- * Ultra Low Light
- * Optical zoom 25 X
- * 1/2.8" Progressive Scan CMOS
- * High resolution 1080p@25 fps - 2 Megapixels
- * 360° Continuous rotation
- * Flip + Mirror Functions
- * No initialisation of the pan/tilt cycle at start-up
- * Passive PoE 12VDC
- * IP
- * 2-year warranty

Specifications:

HERMES	
Image Sensor	1/2.8" Progressive Scan CMOS ULL
Resolution	1080p
Zoom	Optical zoom 25x
Focal length	4.8 to 120 mm
View Angle	57.6° to 2.5° (Wide-Tele)
Mini. Operating distance	10mm to 1500mm (Wide-tele)
Day / Night	ICR Filter
Shutter	1/1 sec to 1/30,000 sec
Minimum Illumination	Colour: 0.05Lux @ (F1.6, AGC ON) B/W: 0.01Lux @ (F1.6, AGC ON)
BLC	Auto
Focus	Auto / Manuel
Network Protocols	RS485 Pelco-D Addresses: 1~4 Speed: 2400/9600
Functions	Flip / Mirror
Power Requirements	12 VDC / 4.5W max
Protection	IP67
Housing	Delrin (POM) Black anodized aluminium
Working Temperature	-5°C to +55°C
Colour	Black
Dimensions	Ø 75mm X 226 mm
Weight	1.15 Kg (without the tactical case)
Transport	Tactical Pelicase 1400
Warranty	2 years

Allwan Security, the leading developer and manufacturer of surveillance and security solutions has launched a new HD-IP periscope camera. Designed for Police/Gendarmerie applications and covering a wide range of mobile and fixed surveillance operations, the Hermes offers reliable and flexible performance in all weather conditions.

It includes an Ethernet and analogue interface and has a resolution of 1080p at 25 fps.

This camera has full PTZ functionality with 360° pan and 60° tilt with continuous rotation.

This new HD-IP camera can be easily concealed in drainpipes, lampposts or integrated into vehicles to provide high quality images to meet individual tactical surveillance requirements.

Allwan Security also offers a 4G tactical case for recording and transmission.



SURVEILLANCE



DÉFENSE



TRANSMISSION



DÉVELOPPEMENT