

GZ36XTR

Marine grade fixed camera station for marine and industry

NDAA Compliant – IP ONVIF – Rugged shock/vibration proof



 AISI 316L 2MP Network Camera	 Optical 36X Zoom, 6 – 216mm	 Night Vision Up To 100M
 Built In Wiper	 -40°C – 60°C	 CE / FCC / KC
 NDAA Compliance		

Marine-grade stainless steel camera by ALLWAN SECURITY.

Fixed, equipped with a motorized 36x zoom and infrared night vision.

Developed to withstand salty sea spray.

In compliance with NDAA, this camera ensures security and confidentiality of the monitored sites.

Highlights :

- Anti-corrosion, electropolished AISI316L stainless steel
- Waterproof IP66/67
- 2Mp H.265
- 36x optical zoom (56.5°~2.1°)
- Built-in IR illuminator 100m
- Shock and vibration resistant
- Heated and ventilated: no fogging
- 24VDC
- Temperature range : -40 to +60°C

Specification :

GZ36XTR : SST 316L fixed camera unit – Extreme areas motorized camera	
CAMERA	
Material	AISI 316L Stainless steel - Electro-polished
Certifications	IP66/67 Tested shocks/vibrations MIL-STD-810G CE/FCC/KC
Sensor	SONY EXMOR CMOS Progressive DAY/NIGHT
Zoom	36x optical 6.0-216mm + 8x Digital
Angle of view	56.5 ~ 2.1°
Shutter	1/30000~1/30sec
Illumination	Color : 0,05Lux BW : 0Lux IR ON
Image settings	DOL HDR, DNR, BLC, HLC, White balance, Exposure, Mirror, Flip, Masking, LDC, OSD
Analysis	Motion detection, Tamper
Pan Tilt	NO
VIDEO	
Compression	H.265, H.264, MJPEG
Resolution	1920x1080, 1280x720, 1024x576, 768x432, 704x392, 640x360, 384x216 at 50/60fps
Streaming	H.265, H.264et MJPEG (Triple streaming) Independent Frame Rate and Bandwidth Control, VBR/CBR
RESEAU	
Security	Multi User Authority, IP Filtering, HTTPS
Protocols	TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, QoS FTP, PnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour
API	Open API, ONVIF profile S/T
GENERAL	
Connectors	One 3/4" NPT conduit entries Ethernet RJ-45(10/100/1000Base-T) Power 2pin terminal block
Power Supply	24VDC
Consumption	50W (80W with optional water tank)
Humidity	0-90% RH(Non-condensing)
Temperature	-40°C - +60°C
Ingress Protection	IP66/67
Dimensions / Weight	152 x 231 x 355mm – 5.6Kg